

NOVAX Material & Technology Safety Data Sheet (SDS)




Safety Data Sheet (SDS)

I - Chemical Product and Company Identification

Product Name : AUS 40
Other Name : Aqueous urea solution 40 - AUS 40
Product Use : Aqueous urea solution 40 or AUS 40 is the other type of DEF usually used for ships. It reduces Nitrogen Oxide (NOx) emissions from vessels and sometimes from the other diesel engine exhaust systems.
Manufacturer/Supplier : NOVAX Material & Technology Inc. No.31, Ln. 142, Sec.2, Nankan Rd., Luzhu Dist., Taoyuan City 33855, Taiwan (R.O.C.) TEL: +886-3-3115988 FAX: +886-3-3115288 E-mail: yang@novax-material.com
Emergency Tel. Number: 0800-200669 / (03) 311-5288

II - Hazards Identification

Classification of the substance or mixture Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008
Label elements Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008
Content of Symbols :  <ul style="list-style-type: none">● Signs & Symptoms :● Signal Words : Warning● Hazard Statements :<ol style="list-style-type: none">1. Harmful if ingested2. Harmful if Skin contacted3. Skin irritation is incurred4. Eye irritation is incurred● Precautionary Statements :<ol style="list-style-type: none">1. Keep away from flammable materials-firework are strictly forbade.2. Put containers in appropriate place along with adequate ventilation.3. Set up electricity preventing methods as operating.
Other Hazards : --

III - Composition, Information on Ingredient Substance

Ingredient	CAS Number	EC Number	%
Urea	57-13-6	200-315-5	40%
Water	7732-18-5	231-791-2	60%

IV ․ First Aid Measures

Emergency Procedures :

- Inhalation :

Remove personnel from exposure area to fresh air immediately. If breathing ceases, use bag-valve resuscitator or similar device to perform artificial respiration. Keep warm and at rest. Get medical attention immediately.

- Skin Contact :

Wash if need. If frostbite, freezing, or cryogenic burns occur, warm affected area in warm water. If this is not available, gently wrap affected parts in blankets. Allow circulation to return naturally. Get medical attention immediately.

- Eye Contact :

Wash with large amounts of water or normal saline until no evidence of chemical remains (at least 15~20 minutes). Get medical attention immediately.

- Ingestion :

It is unlikely that emergency treatment will be required. Get medical attention, if need.

V ․ First Fighting Measures

- Suitable Extinguishing Media :

In case of fire, use water spray (fog), foam, dry chemical or CO₂.

- Specific Hazards :

1. Non-flammable by decomposition product of carbon dioxide (CO₂), carbon monoxide (CO), nitrogen oxides (NO_x), ammonia (NH₃).
2. Ambient fire might occur hazard steam, and probably related Nitrogen Oxides is incurred once on fire.

- Specific Fire Fighting Procedure :

1. Move container away from fire area if it can be done without risk.
2. Cool containers with water spray until well after the fire is out.
3. Keep unnecessary people away, isolate hazard area and deny entry.

- Specific Fire Fighting Equipment :

1. Fire fighters should thermal protective clothing and self-contained breathing apparatus.
2. Fire fighters should not access airtight spaces without wearing self-contained breathing apparatus and thermal protective clothing.

VI - Accidental Release Measures

- Personal Precautions :
 1. Avoid heat, flames, sparks and other sources of ignition.
 2. Don't touch spilled material.
 3. Stay at downwind, and keep away from low-lying area.
- Environmental Precautions :
 1. Keep away from headwaters or sewer.
 2. Eliminate all open flame in vicinity of spill or released vapor.
 3. Keep unnecessary people away, isolate hazard area and deny entry.
 4. Ventilate closed spaces before entering.
- Methods for Cleaning up :
 1. Take out material after dry or scrap.
 2. Clean up effected area by running water.

VII - Handling and Storage :

- Handling :

Wear suitable protective equipment.

When using the product do not eat, drink or smoke.

Use according to industrial hygiene rules.

Make sure operation is under ventilate environment.
- Storage :

Use according to industrial hygiene regulations.

Store in a closed container away from incompatible.

Keep drying and container closing.

Check remarkable label onto container.

Avoid physical damage and spill of container.

Suggest storage temperature is 25°C .

VIII - Exposure Controls and Personal Protection :

- Engineering Control :

Ensure adequate ventilation, especially in confined areas. Use only under good ventilation conditions or with respiratory protection.
- Control Parameter :

TWA	STEL	CEILING	BEIS
Not established	Not established	Not established	Not established

Safety Data Sheet (SDS)

● Personal Protection Equipment :

1. Eye : Wear safety glasses with side shields. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.
2. Hand : Impervious gloves. Wash hands before breaks and immediately after handling the product.
3. Skin and Body : Protecting clothing.
4. Respiratory : At high concentration, any supplied-air respirator with a sanitary mask even full face piece is required. Notice on warning matter while using.
5. General hygiene considerations : Avoid breathing vapors. Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink.

IX 、 Physical and Chemical Properties

Physical State and Appearance :	liquid	Odor :	slight ammonia
Odor Threshold Value :	--	Melting Point :	133 - 135°C
pH Value :	8~10	Boiling Point/Boiling Range :	--
Flammability Classification (Solid 、 Gas) :	--	Flash Point :	--
Decomposition Temperature :	--	Test Method :	closed cup
Auto-ignition Temperature :	--	Flammable Limits :	--
Vapor Pressure (20°C) :	<0.1hPa	Vapor Density :	--
Density (20°C) :	1.105~1.177g/cm ³	Solubility (water) :	--
Octanol/H ₂ O Coeff. (log Kow) :	--	Evaporation Rate (N-Butyl Acetate=1) :	--

X 、 Stability and Reactivity

- Stability : Stable under recommended storage conditions.
- Possible Hazardous Reactions : --
- Conditions to Avoid : Don't mix with any other chemical or product.
- Materials to Avoid : Acids, Oxidizers, Alkalis.
- Hazardous Decomposition Products : Ammonia gas may be released at high temperatures. Burring of the product releases CO, CO₂, NO_x.

XI 、 Toxicological Information

- Routes of Exposure : Skin, eye, inhalation, ingestion
- Main Symptoms : As statement below.
- Acute Toxicity :
 1. Inhalation : Not available.
 2. Skin Contact : May cause irritation.
 3. Eye Contact : May cause irritation.
 4. Ingestion : May cause stomach distress, nausea or vomiting.

- Chronic Toxicity :

1. Inhalation : No data available.
2. Skin Contact : Repetitive contact will induce the similar symptom of acute toxicity.
3. Eye Contact : Repetitive contact will induce the similar symptom of acute toxicity.
4. Ingestion : No data available.

- Toxicity Information :

1. LD₅₀ (Rats, Skin) : 8200 mg/kg oral dose of rates
2. LD₅₀ (Rats, Ingestion) : 8471 mg/kg oral dose of rates

XII 、 Ecological Information

- Eco-toxicity : Components of this product have been identified as having potential environment concerns.

1. Fish toxicity : L.idus, LC50 : > 6810 mg/L /96h
2. Daphnia toxicity : Daphnia magna, EC50 : > 10000 mg/L /24
3. Toxic algae : Sc.quadricauda IC5 : > 100000 mg/L / 1 / 7d
4. Bacterial toxicity : Ps.putida EC50 : > 100000 mg/L / 16h

- Persistence/Degradability : Not available.
- Bio-accumulate/Accumulation : Not available.
- Mobility in Soil : Not available.
- Other Harmful Effects : Not available.

XIII 、 Disposal Considerations

- Method of disposal :

Empty containers or liners may retain some product residues. Do not empty into drains ; dispose of this material and its container in a safe way. Dispose of in accordance with all applicable local national regulations.

- Hazardous waste :

Disposal according to local regulations.

XIV 、 Transport Information

UN/NA : --
Shipping Name : --
Hazard Class : --
Required Label(s) : --
Packing Group : --
Pollution of Sea (yes/no) : No

Specific Shipping Requirements :

1. Transport state : Liquid
2. Storage Temperature : Room temperature
3. Pipeline Material : Bag, barrel, tank, tanker, truck, train, bulk carrier.
4. Packing Requirement : Sealed package to avoid concentration deduction caused by moisture absorption.

XV 、Regulation Information

Suitable Regulations of R.O.C :

1. Occupational Safety and Health Act
2. Standards of Permissible Exposure Limits of Airborne Hazardous Substances in Workplace
3. Labor Safety and Health Act
4. Regulation of Labeling and Hazard Communication of Dangerous and Harmful Materials
5. Act Governing the Punishment of Violation of Road Traffic Regulations
6. Toxicity Chemical Indication and Safety Data Sheets Management
7. Criteria Governing Methods of and Facilities for Storage, Clearance and Disposal of Industrial Wastes

XVI 、Other Information

Reference Literatures :

1. Council of Labor Affairs Material Safety Data Sheets
2. ITRI (industrial technology research institute) Industry Safety and Health Technology Center
3. Database of Science Lab.com, U.S.A

Made By : NOVAX Material & Technology Inc.

Ms. Maggie Chen | Laboratory Analysis and QC Hosting

Ms. Janformy Wu | General Manager's Office

Creation Date : 2023.08.08

Remark : Foregoing statement including symbol "—" means: No data at present.

NOVAX Material & Technology Inc, Taiwan believes that the information contained herein (including data and statements) is accurate as of the date hereof. **NO ANY WARRANTY, EXPRESS OR IMPLIED, IS MADE AS CONCERNS THE INFORMATION HEREIN PROVIDED.** The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use of the product and information referred to herein are beyond the control of NOVAX expressly disclaims any and all liability as to any results obtained or arising from any use of product or such information.